

SPECIFICATIONS

SPECIFICATIONS

< FM Section >

Receiving Frequency:	87.5MHz – 108MHz	
50dB Quieting Sensitivity:	75 μ sec. 14.2 dBf (2.8 μ V), 50 μ sec. 14.8 dBf (3.0 μ V)	
IHF Usable Sensitivity:	10.3 dBf (1.8 μ V)	
Signal to Noise Ratio:	75 dB	
Frequency Response:	30 – 15 kHz (within \pm 1 dB)	
Total Harmonic Distortion	(mono)	(stereo)
	100Hz:	0.08% (wide) 0.2% (wide)
	1kHz:	0.08% (wide) 0.15% (wide)
	6kHz:	0.15% (wide) 0.3% (wide)
	1kHz:	0.2% (narrow) 0.5% (narrow)
Capture Ratio:	1.0dB (wide)	2.0dB (narrow)
Adjacent Channel Selectivity:	10dB (narrow \pm 200kHz)	
Alternate Channel Selectivity:	80dB (narrow \pm 400kHz)	
	40dB (wide \pm 400kHz)	
Spurious Response Ratio:	80dB	
IF Response Ratio:	80dB	
Image Response Ratio:	55dB	
AM Suppression Ratio:	60dB	
Stereo Separation:	45dB (wide, 100Hz), 48dB (wide, 1kHz)	
	40dB (wide, 10kHz), 30dB (narrow 1kHz)	
Subsonic Product Ratio:	65dB	
SCA Rejection Ratio:	60dB	
Output Voltage:	1V	
Output Impedance:	100 ohms	
Muting Threshold:	10 μ V – 300 μ V	

< AM Section >

IHF Usable Sensitivity:	250 μ V/m
Image Ratio at 1MHz:	50dB
IF Rejection Ratio at 1MHz:	40dB
Signal to Noise Ratio:	50dB
Total Harmonic Distortion:	0.6%
Output Voltage 30% mod.:	0.3V
Power Requirement:	10W
Additional Features:	Tuning Lock System, CLL Circuit, IF Bandwidth Selector. Center Indicator, Signal Strength Indicator, FM Muting Switch. FM Muting Level Adjuster
Dimensions:	466(W) x 350(D) x 120(H) mm (18-11/32" x 13-25/32" x 4-23/32") (including legs and rear protrusions)
Weight:	Net: 6.5 kgs (14.3 lbs.) Gross: 8.0kgs (17.6 lbs.)

Specifications and appearance design subject to change without notice.